

GE Rod end GAR40-UK-2RS-DURBAL - GAR40-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/ge/gar40-uk-2rs-durbal>


GAR40-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)	
right-hand thread	d	G
left-hand thread	B	C1
GAR 40 UK-2RS	40	M 39 x 3
	28	23,0
		92

type	measurement [mm]			load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min	h		
GAR / GAL 40 UK-2RS	86	48	150	180,0	1,800

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467652
Inside diameter	40 mm
Outside diameter	92 mm
Thickness	28 mm
Type	GE
Weight	1800 g
Thread	Right-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE