

GE Rod end GAL45-UK-2RS-DURBAL - DGAL45-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/ge/dgal45-uk-2rs-durbal>


GAL45-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	measurement (mm)	C ₁	d ₂
GAL 45 UK-2RS	45	M 42 x 3	32	27,0	102

type	l ₁ min	measurement (mm) l ₂ min	h	α [°]	load rating C ₀ [kN]	weight (kg)
GAR / GAL 45 UK-2RS	94	52	163	7	240,0	2,600

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467690
Inside diameter	45 mm
Outside diameter	102 mm
Thickness	32 mm
Type	GE
Weight	2600 g
Thread	Left-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE