

GE Rod end GAR50-UK-2RS-DURBAL - GAR50-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/ge/gar50-uk-2rs-durbal>


GAR50-UK-2RS



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGEAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)					
right hand thread	d	G	S	C1	d2	
GAR 50 UK-2RS	50	M 45 x 3	35	30,0	112	

type	l1 min	measurement (mm)	h	alpha [°]	load rating C0 (kN)	weight (kg)
GAR / GAL 50 UK-2RS	107	60	185	6	290,0	3,400

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467737
Inside diameter	50 mm
Outside diameter	112 mm
Thickness	35 mm
Type	GE
Weight	3400 g
Thread	Right-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE