

GE Rod end GAL60-UK-2RS-DURBAL - GAL60-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/ge/gal60-uk-2rs-durbal>


GAL60-UK-2RS



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	B	C1	d2
right hand thread					
left hand thread					
GAL 60 UK-2RS	60	M 52 x 3	44	38,0	135

type	l, min	measurement [mm] l, min	h	alpha [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 60 UK-2RS	115	75	210	6	450,0	5,900

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467775
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	GE
Weight	5900 g
Thread	Left-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE