

SI Rod end GIL8-UK-DURBAL - GIL8-UK-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/gil8-uk-durbal>

GIL8-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination: steel / bronze-PTFE fabric

Rod end body: surface zinc plated

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	measurement [mm]	
GIL 8 UK	6,0	24

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	t_2 min	h	W			
GIR / GIL 8 UK	15	36	14	15	12,9	0,039

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493619
Inside diameter	8 mm
Outside diameter	24 mm
Thickness	8 mm
Type	SI
Weight	39 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE