

SI Rod end GIR12-UK-DURBAL - GIR12-UK-DURBAL

https://www.123bearing.eu/bearing-housing/rod-end/si/gir12-uk-durbal

GIR12-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]					
d	G	B	C ₁	C ₂	d ₂	d ₄		
GIR 12 UK	12	M 12	10	8,0	34	17,5	22	

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIR 12 UK	23	50	19	11	24,5	0,096

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493695
Inside diameter	12 mm
Outside diameter	34 mm
Thickness	10 mm
Type	SI
Weight	96 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE