

SI Rod end GIR25-UK-DURBAL - GIR25-UK-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/gir25-uk-durbal>

GIR25-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	C ₁	C ₂	d ₂	d ₄
GIR 25 UK	25	M 24 x 2	20	17,0	64	33,5	42

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIR 25 UK	48	94	36	7	83,0	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493978
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SI
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE