

SI Rod end GIL30-UK-2RS-DURBAL - DGIL30-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dgil30-uk-2rs-durbal>

GIL30-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination: steel / bronze-PTFE fabric

Rod end body: surface zinc plated

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]			
right hand thread				C ₁	d ₂	d ₃	d ₄
GIL 30 UK (-2RS)	30	M 30 x 2	22	19,0	73	40,0	50

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 30 UK	56	110	41	6	110,0	0,930

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494043
Inside diameter	30 mm
Outside diameter	73 mm
Thickness	22 mm
Type	SI
Weight	930 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE