

SI Rod end GIR45-UK-2RS-DURBAL - GIR45-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/gir45-uk-2rs-durbal>

GIR45-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]			
GIR 45 UK-2RS	d 45	G M 42 x 3		
	B 32	C ₁ 27,0		
	d ₂ 102	d ₄ 70		
type	measurement [mm]		load rating	weight
GIR / GIL 45 UK-2RS	t _{3 min} 65	h 145	C ₀ (kN) 240,0	[kg] 2,500

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494166
Inside diameter	45 mm
Inside diameter	1.772" inch
Outside diameter	102 mm
Outside diameter	4.016" inch
Thickness	32 mm
Thickness	1.26" inch
Type	SI
Weight	2500 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE