

# SI Rod end GIL50-UK-2RS-DURBAL - GIL50-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/gil50-uk-2rs-durbal>

## GIL50-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Sliding combination:** steel / bronze-PTFE fabric

**Rod end body:** surface zinc plated

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIL 50 UK-2RS	50	M 45 x 3	35	30,0	112	62,0	75

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIL 50 UK-2RS	68	160	65	6	290,0	3,500

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494203
Inside diameter	50 mm
Outside diameter	112 mm
Thickness	35 mm
Type	SI
Weight	3500 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE