

SI Rod end GIR80-UK-2RS-DURBAL - GIR80-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/gir80-uk-2rs-durbal>

GIR80-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]	
GIR 80 UK-2RS	d 80	G M 64 x 4
	B 55	C1 47,0
		d2 180
		d3 95,0
		d4 110

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	t_2 min	h	W			
GIR / GIR 80 UK-2RS	85	230	100	6	750,0	12,000

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494326
Inside diameter	80 mm
Outside diameter	180 mm
Thickness	55 mm
Type	SI
Weight	12000 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE