

SA Rod end POSL5-DURBAL - POSL5-DURBAL


<https://www.123bearing.eu/bearing-housing/rod-end/sa/posl5-durbal>

POSL5



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required

order number		measurement [mm]			
right hand thread	left hand thread	B	G	C ₁	d ₁
POSL 5		5	M 5	8	6,00 16

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
POS / POSL 5	20	33	13	5,7	0,013

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494371
Inside diameter	5 mm
Outside diameter	16 mm
Thickness	8 mm
Type	SA
Weight	13 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE