

## SA Rod end POSL22-DURBAL - POSL22-DURBAL


<https://www.123bearing.eu/bearing-housing/rod-end/sa/posl22-durbal>

### POSL22



**Description:** DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Rod end body:  
surface zinc plated

Sliding combination:  
steel / heavy duty bronze

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
heavy duty bronze with lubrication

Lubrication:  
lubrication required

order number	measurement [mm]		B	C <sub>1</sub>	d <sub>1</sub>
	right hand thread	left hand thread			
POSL 22	22	M 22 x 1,5	28	20,00	54

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
POS / POSL 22	51	84	15	57,0	0,480

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494739
Inside diameter	22 mm
Inside diameter	0.866" inch
Outside diameter	54 mm
Outside diameter	2.126" inch
Thickness	28 mm
Thickness	1.102" inch
Type	SA
Weight	480 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE