

SI Rod end

SIZPL15-S-DURBAL - SIZPL15-S-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/sizpl15-s-durbal>

SIZPL15-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

Rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIZPL 15 S		15,88	5/8 - 18	19,05	14,27	38,10	21,84	25,40

type		inches	measurement [mm]			alpha [°]	load rating C ₀ [kN]	weight [kg]
			l ₁ min	W	h			
SIZP /	SIZPL 15 S	5 / 8 "	38,10	22,23	63,50	11	21,0	0,190

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952495873
Inside diameter	15.88 mm
Inside diameter	5/8" inch
Outside diameter	38.1 mm
Outside diameter	1 1/2" inch
Thickness	19.05 mm
Thickness	3/4" inch
Type	SI
Weight	190 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE