

SA Rod end DSAZPL4-S-DURBAL - DSAZPL4-S-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/dsazpl4-s-durbal>


DSAZPL4-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.



Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
DSAZPL 4 S		4,83	10 - 32	7,92	6,35	15,88

type	inches	measurement [mm]		load rating	weight
		l ₁ min	h	C ₀ [kN]	W [g]
DSAZP / DSAZPL 4 S		19,05	31,75	10	0,013

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496009
Inside diameter	4.83 mm
Outside diameter	15.88 mm
Thickness	7.92 mm
Type	SA
Weight	13 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE