

SA Rod end
SAZP15-S-DURBAL - SAZP15-S-DURBAL
<https://www.123bearing.eu/bearing-housing/rod-end/sa/sazp15-s-durbal>

SAZP15-S



male thread:
lubrication required, similar to DIN ISO 12240-4; series R, measurement in inches

Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SAZP 15 S		15,88	5/8 - 18
			B
			19,05
			C1
			14,27
			d2
			38,10

type	inches	measurement [mm]		load rating	weight
		l min	h	C0 [kN]	lkg
SAZP / SAZPL 15 S	5 / 8 "	41,28	66,68	11	0,180

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496221
Inside diameter	15.88 mm
Outside diameter	38.1 mm
Thickness	19.05 mm
Type	SA
Weight	180 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE