

SA Rod end DSAZPL25-S-DURBAL - DSAZPL25-S-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/dsazpl25-s-durbal>

DSAZPL25-S



male thread:
lubrication required, similar to DIN ISO 12240-4; series R, measurement in inches

Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]	
right hand thread	left hand thread	d	G
DSAZPL 25 S		25,40	34,93

type	inches	measurement [mm]		load rating C ₀ [kN]	weight [g]
		h [mm]	α [°]		
DSAZP / DSAZPL 25 S	1"	53,98	104,78	14	1,100

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496320
Inside diameter	25.4 mm
Outside diameter	69.85 mm
Thickness	34.93 mm
Type	SA
Weight	1100 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE