

## SA Rod end SAZJL15-DURBAL - SAZJL15-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/sazjl15-durbal>

### SAZJL15



**female thread:**  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions in inch. Housing made of forged steel, sliding combination steel / steel. Size  $\geq 9$  with grease nipple can be mounted upon request.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SAZJL 15		15,88	5/8 - 18	19,05	12,29	38,10

type	inches	measurement [mm]		alpha [°]	load rating C <sub>0</sub> [kN]	weight [g]
		l <sub>1</sub> min	h			
SAZI / SAZJL 15	5 / 8 "	41,28	66,68	13,0	29,0	0,160

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496597
Inside diameter	15.88 mm
Outside diameter	38.1 mm
Thickness	19.05 mm
Type	SA
Weight	160 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE