

## SI Rod end SIZJL4-DURBAL - SIZJL4-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/sizjl4-durbal>

### SIZJL4



**female thread:**  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size ≥ 9 with grease nipple can be mounted upon  
request.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number	right hand thread	left hand thread	measurement [mm]					
	d	B	C1	d2	G	d3	d4	
<b>SIZJL 4</b>	4,83	7,92	5,94	15,88	10 - 32	7,54	10,31	

type	inches	h <sub>1</sub> min	measurement [mm]		α	load rating	weight
			W	h	[°]	C <sub>0</sub> [kN]	[kg]
<b>SIZJ / SIZJL 4</b>		12,70	7,92	26,97	10,0	6,8	0,018

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496672
Inside diameter	4.83 mm
Inside diameter	0.19" inch
Outside diameter	15.88 mm
Outside diameter	5/8" inch
Thickness	7.92 mm
Thickness	0.312" inch
Type	SI
Weight	18 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE