

## SI Rod end DSIZJ6-DURBAL - DSIZJ6-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dsizj6-durbal>


### DSIZJ6



female thread;  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches



**Description:** DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / steel. Size  $\geq 9$  with grease nipple can be mounted upon request.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number	right hand thread	left hand thread	measurement [mm]					
	d	B	C <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>	
DSIZJ 6	6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91	

type	inches	h <sub>1</sub> min	measurement [mm]		α	load rating	weight
			W	h	[°]	C <sub>0</sub> [kN]	[g]
DSIZJ / DSIZJL 6	1 / 4 "	15,88	9,53	33,32	13,5	9,6	0,023

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496726
Inside diameter	6.35 mm
Outside diameter	19.05 mm
Thickness	9.53 mm
Type	SI
Weight	23 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE