

## SI Rod end SIZJ9-DURBAL - DSIZJ9-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dsizj9-durbal>


### SIZJ9



female thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches



**Description:** DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / steel.  
Size: 9 with grease nipple can be mounted upon request.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number		measurement [mm]						
right hand thread	left hand thread	d	B	C <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>
SIZJ 9		9,53	12,70	9,12	25,40	3/8 - 24	13,89	17,45

type		measurement [mm]				load rating	weight
inches	h <sub>1</sub> min	W	h	α [°]	C <sub>0</sub> [kN]	[kg]	
SIZJ / SIZJL 9	3 / 8"	19,05	14,27	41,28	11,0	16,0	0,059

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496795
Inside diameter	9.53 mm
Outside diameter	25.4 mm
Thickness	12.7 mm
Type	SI
Weight	59 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE