

SI Rod end SIZJ19-DURBAL - DSIZJ19-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dsizj19-durbal>


SIZJ19



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number	d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJ 19	19,05	22,23	15,06	44,45	3/4 - 16	25,02	28,58

type	inches	h ₁ min	W	h	α [°]	load rating C ₀ (kN)	weight (kg)
SIZJ / SIZJL 19	3 / 4 "	34,93	25,40	73,03	12,0	44,0	0,295

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496955
Inside diameter	19.05 mm
Outside diameter	44.45 mm
Thickness	22.23 mm
Type	SI
Weight	295 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE