

SI Rod end SI17-ES-DURBAL - SI17-ES-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/si17-es-durbal>

SI17-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

Rod end body:
surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 17 ES		17	M 16	14	11,0	46	24,0	30

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [g]
	l_1 min	W	h			
SI / SII 17 ES	34	27	67	10	45,0	0,22

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496986
Inside diameter	17 mm
Outside diameter	46 mm
Thickness	14 mm
Type	SI
Weight	220 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE