

SI Rod end SI25-ES-2RS-DURBAL - SI25-ES-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/si25-es-2rs-durbal>

SI25-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SI 25 ES (-2RS)	measurement (mm)	
	d	G
	25	M 24 x 2

measurement (mm)

type	measurement [mm]				load rating C_0 [kN]	weight [kg]
	l_1 min	W	h	α [°]		
SI / SII 25 ES (-2RS)	48	36	94	7	83,0	0,64

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497198
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SI
Weight	640 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE