

SI Rod end SIL30-ES-2RS-DURBAL - SIL30-ES-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/sil30-es-2rs-durbal>

SIL30-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

Rod end body:
surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIL 30 ES (-2RS)		30	M 30 x 2	22	19,0	73	40,0	50

type	measurement [mm]			load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h		
SI / SIL 30 ES (-2RS)	56	41	110	6	110,0

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497273
Inside diameter	30 mm
Outside diameter	73 mm
Thickness	22 mm
Type	SI
Weight	930 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE