

## SI Rod end SIL35-ES-DURBAL - SIL35-ES-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/sil35-es-durbal>

### SIL35-ES



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2/R5 with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**Rod end body:**  
surface zinc plated

order number		measurement (mm)									
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4	h	W	alpha
	<b>SIL 35 ES</b>	35	M 36 x 3	25	21,0	82	47,0	58			

type	measurement [mm]					load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h	alpha [°]			
SI / SIL 35 ES	60	50	125	6	146,0	1,3	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497310
Inside diameter	35 mm
Outside diameter	82 mm
Thickness	25 mm
Type	SI
Weight	1300 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE