

## SI Rod end SIL45-ES-2RS-DURBAL - DSIL45-ES-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dsil45-es-2rs-durbal>

### SIL45-ES-2RS



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSIL...ES-2RS with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**Rod end body:** surface zinc plated

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIL 45 ES (-2RS)		45	M 42 x 3	32	27,0	102	58,0	70

type	measurement [mm]			$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h			
SI / SIL 45 ES (-2RS)	65	60	145	7	240,0	2,5

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497464
Inside diameter	45 mm
Outside diameter	102 mm
Thickness	32 mm
Type	SI
Weight	2500 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE