

SI Rod end SIL60-ES-DURBAL - SIL60-ES-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/sil60-es-durbal>

SIL60-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

Rod end body:
surface zinc plated

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 60 ES		60	M 52 x 3

type	measurement [mm]			α [°]	load rating C_p [kN]	weight [kg]
	l_1 min	W	h			
SI / SIL 60 ES	70	75	175	6	450,0	5,5

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497631
Inside diameter	60 mm
Inside diameter	2.362" inch
Outside diameter	135 mm
Outside diameter	5.315" inch
Thickness	44 mm
Thickness	1.732" inch
Type	SI
Weight	5500 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE