

SA Rod end SAL17-ES-DURBAL - SAL17-ES-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/sal17-es-durbal>

SAL17-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 17 ES	17	M 16	14	11,0	46

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 17 ES	36	23	69	10	45,0	0,190	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498102
Inside diameter	17 mm
Outside diameter	46 mm
Thickness	14 mm
Type	SA
Weight	190 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE