

SA Rod end SA17-ES-DURBAL - DSA17-ES-DURBAL

https://www.123bearing.eu/bearing-housing/rod-end/sa/dsa17-es-durbal

SA17-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| SA 17 ES | | 17 | M 16 | 14 | 11,0 | 46 |

| type | measurement [mm] | | | n [°] | load rating C ₀ [kN] | weight [kg] |
|-----------------|--------------------|----------------|----|----------|---------------------------------------|----------------|
| | l ₁ min | l ₂ | h | | | |
| SA / SA L 17 ES | 36 | 23 | 69 | 10 | 45,0 | 0,190 |

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952498157 |
| Inside diameter | 17 mm |
| Outside diameter | 46 mm |
| Thickness | 14 mm |
| Type | SA |
| Weight | 190 g |
| Thread | Right-hand thread |
| Lubrication | with |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE