

SA Rod end SAL45-ES-2RS-DURBAL - SAL45-ES-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/sal45-es-2rs-durbal>

SAL45-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 45 ES (-2RS)	45	M 42 x 3	32	27,0	102	

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h	n [°]		
SA / SAL 45 ES (-2RS)	94	51	163	7	240,0	2,600

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498584
Inside diameter	45 mm
Outside diameter	102 mm
Thickness	32 mm
Type	SA
Weight	2600 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE