

SA Rod end SA60-ES-2RS-DURBAL - SA60-ES-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/sa60-es-2rs-durbal>

SA60-ES-2RS



**male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E**

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 60 ES (-2RS)		60	M 52 x 3	44	38,0	135

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 60 ES (-2RS)	115	60	210	6	6	450,0	5,900

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498799
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	SA
Weight	5900 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE