

## SA Rod end SA70-ES-DURBAL - SA70-ES-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/sa70-es-durbal>

### SA70-ES



**male thread: lubrication is necessary, according to DIN ISO 12240-4, series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

**Ball end body:** surface zinc plated

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 70 ES		70	M 56 x 4	49	42,0	160

type	measurement [mm]				n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h				
SA / SA L 70 ES	125	80	235		6	610,0	8,200

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498836
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SA
Weight	8200 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE