TAPR Rod end
GIHO-K-12DO-DURBAL - GIHO-K-12DO-DURBAL

https://www.123bearing.eu/bearing-housing/rod-end/tapr/giho-k-12do-durbal



GIHO-K-12DO

FERROBAL

* without grease nipple

Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE.. ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

female thread; hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number (right hand thread / left hand thread)	d	d_1	d_2	G	d_4	d_5	B	C_1	C_2
GIHO-K 12 DO*	12	15,0	35	M 10 x 1,25	17	40	10	8	13

type	h_1	l_2	l_4	l_7	α [°]	load rating C_0 [kN]	weight [kg]
GIHO-K / GIHO-KL 12 DO*	42	15	59,5	16	11	17,0	0,12

123BEARING

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500607
Inside diameter	12 mm
Outside diameter	35 mm
Thickness	8 mm
Type	TAPR
Weight	120 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE