

TAPR Rod end GIHO-KL-12DO-DURBAL - GIHO-KL-12DO-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/tapr/giho-kl-12do-durbal>

GIHO-KL-12DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]		
right hand thread	left hand thread		
GIHO-KL 12 DO*			
	12	15,0	35
	M 10 x 1,25	17	40
	10	8	13

type	measurement [mm]				α [°]	load rating C_0 [kN]	weight [kg]
	h_1	l_1	l_2	l_3			
GIHO-K / GIHO-KL 12 DO*	42	15	59,5	16	11	17,0	0,12

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500614
Inside diameter	12 mm
Outside diameter	35 mm
Thickness	8 mm
Type	TAPR
Weight	120 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE