

## TAPR Rod end GIHO-K-16DO-DURBAL - GIHO-K-16DO-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/tapr/giho-k-16do-durbal>

### GIHO-K-16DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	measurement [mm]									
right hand thread	left hand thread	d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>4</sub>	d <sub>5</sub>	B	C <sub>1</sub>	C <sub>2</sub>
GIHO-K 16 DO*		16	20,7	45	M 12 x 1,25	21	45	14	11	13

type	measurement [mm]				α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>			
GIHO-K / GIHO-KL 16 DO	48	17	70,5	20	10	28,5	0,22

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500652
Inside diameter	16 mm
Outside diameter	45 mm
Thickness	11 mm
Type	TAPR
Weight	220 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE