

## TAPR Rod end GIHO-K-20DO-DURBAL - GIHO-K-20DO-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/tapr/giho-k-20do-durbal>

### GIHO-K-20DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-K 20 DO*		
	20	24,1 55 M 14 x 1,5 25 55 16 13 17

type	measurement [mm]			$\alpha$	load rating	weight	
	$h_1$	$l_1$	$l_2$	[°]	$C_0$ [kN]	[kg]	
GIHO-K / GIHO-KL 20 DO	58	19	85,5	25	9	42,5	0,43

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500683
Inside diameter	20 mm
Outside diameter	55 mm
Thickness	13 mm
Type	TAPR
Weight	430 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE