

TAPR Rod end GIHO-K-25DO-DURBAL - GIHO-K-25DO-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/tapr/giho-k-25do-durbal>

GIHO-K-25DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-K 25 DO	25	25,3 65 M 16 x 1,5 30 62 20 17 17

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
GIHO-K / GIHO-KL 25 DO	68	23	100,5	30	7	67,0

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500737
Inside diameter	25 mm
Outside diameter	65 mm
Thickness	17 mm
Type	TAPR
Weight	670 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE