

# TAPR Rod end GIHO-KL-40DO-DURBAL - GIHO-KL-40DO-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/tapr/giho-kl-40do-durbal>

## GIHO-KL-40DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>4</sub>	d <sub>5</sub>	B	C <sub>1</sub>	C <sub>2</sub>	
GIHO-KL 40 DO		40	45,0	100	M 27 x 2	45	90	28	23	23	

type	measurement [mm]				α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>			
GIHN-K / GIHN-KL 40 DO	105	37	155,0	45	7	156,0	2,16

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500805
Inside diameter	40 mm
Outside diameter	100 mm
Thickness	23 mm
Type	TAPR
Weight	2160 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE