

# TAPR Rod end GIHO-K-60DO-DURBAL - GIHO-K-60DO-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/tapr/giho-k-60do-durbal>

## GIHO-K-60DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	measurement [mm]		
right hand thread	left hand thread		
<b>GIHO-K 60 DO</b>	60	66,8 160 M 42 x 2	68 134 44 38 38

type	measurement [mm]				$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$h_1$	$l_1$	$l_2$	$l_3$			
GIHN-K / GIHN-KL 60 DO	150	57	230,0	68	6	380,0	7,15

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500898
Inside diameter	60 mm
Outside diameter	160 mm
Thickness	38 mm
Type	TAPR
Weight	7150 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE