

TAPR Rod end GIHO-KL-100DO-DURBAL - DGIHO-KL-100DO-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/tapr/djiho-kl-100do-durbal>

GIHO-KL-100DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]		
right hand thread	left hand thread		
GIHO-KL 100 DO	100	109,5	240
	M 64 x 3	110	190
		70	55
		55	55

type	measurement [mm]				α [°]	load rating C_0 [kN]	weight [kg]
	h_1	l_1	l_2	l_3			
GIHN-K / GIHN-KL 100 DO	240	86	360,0	116	6	865,0	27,30

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500966
Inside diameter	100 mm
Outside diameter	240 mm
Thickness	55 mm
Type	TAPR
Weight	27300 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE