

TAPR Rod end GIHO-K-100DO-DURBAL - GIHO-K-100DO-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/tapr/giho-k-100do-durbal>

GIHO-K-100DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-K 100 DO		100	109,5	240	M 64 x 3	110	190	70	55	55	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHN-K / GIHN-KL 100 DO	240	86	360,0	116	6	865,0	27,30

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500973
Inside diameter	100 mm
Outside diameter	240 mm
Thickness	55 mm
Type	TAPR
Weight	27300 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE