


SA Rod end BRM22-00-501-DURBAL - BRM22-00-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/brm22-00-501-durbal>

BRM22-00-501



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex-soap-grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 2455 D11A (sizes 6 to 10)
DIN 21 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial
tolerances:
see page 10

order number		measurements [mm]						
Type	right-hand thread	M1	M2	M3	M4	M5	M6	M7
BRM 22 -00 -501		22	M 22 x 1,5	26,0	54	28	20,0	Ø4
measurements [mm]		weight	calculation- factors	rotational speed limit	basic load rating			
Type	l	l ₃	α [°]	Y	v ₉₀	C	d _{ym}	stat. C ₁₀
BRM 22	51	26	8,0	0,450	2,35	2,24	725	9300 3980

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507088
Inside diameter	22 mm
Outside diameter	54 mm
Thickness	28 mm
Type	SA
Weight	450 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE