


SA Rod end PM06-00-501-DURBAL - PM06-00-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm06-00-501-durbal>


PM06-00-501



male thread:
long-term lubrication, low maintenance, shields



DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating			
type	sp. hand thread	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y _c	C	C ₀
PM 06 -00	-501	6	M 10 x 1	8,5	24	14	14	10					
measurements [mm]		weight		rotational speed limit		basic load rating							
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	Y	Y _c	C	C ₀	C ₀ [N]
PM 06	42,5	17	64	1,5	2,5	10,5	0,062		1,28	1,34	1300	2445	765

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507460
Inside diameter	6 mm
Outside diameter	24 mm
Thickness	14 mm
Type	SA
Weight	62 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE