

SA Rod end PM06-02-502-DURBAL - PM06-02-502-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm06-02-502-durbal>

PM06-02-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]
PM 06 -02	-502	6	M 10 x 1	8,5	24	14	14	14	10				1300	2445	765
type	l1	l2	l3	h1	h2	u	z	alpha [°]	weight [kg]	calculation factors	rotational speed limit	basic load rating	dyn. C [N]	stat. C0 [N]	
PM 06	19	17	40,5	1,5	2,5	10,5	0,057		1,28	1,34	1300	2445	765		

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507484
Inside diameter	6 mm
Outside diameter	24 mm
Thickness	14 mm
Type	SA
Weight	57 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE