

SA Rod end PM10-00-501-DURBAL - PM10-00-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm10-00-501-durbal>

PM10-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]			measurements [mm]		
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	l1	l2	l3
PM 10 -00	-501	10	M 14 x 1,5	13,5	36	19	20	14					

type	measurements [mm]			weight [kg]	calculation factors Y	rotational speed limit [min ⁻¹]	basic load rating		
	l1	l2	l3				C [N]	C0 [N]	
PM 10	49,5	28	82	0,168	1,69	1,77	1100	5120	1905

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507545
Inside diameter	10 mm
Outside diameter	36 mm
Thickness	20 mm
Type	SA
Weight	168 g
Thread	Right-hand thread
Lubrication	with
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE