

SA Rod end PM15-00-501-DURBAL - PM15-00-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm15-00-501-durbal>

PM15-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]							
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3				
PM 15 -00	-501	15	M 20 x 1,5	18,5	42	26	20	14						
measurements [mm]		weight		rotational speed limit		basic load rating		stat.						
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	Yc	nmax [min-1]	C [N]	C0 [N]
PM 15	62,5	30	100	3,0	2,5	6,5	0,310	2,07	2,17			975	5485	3270

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507620
Inside diameter	15 mm
Outside diameter	42 mm
Thickness	20 mm
Type	SA
Weight	310 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE