

## SA Rod end PM15-02-502-DURBAL - PM15-02-502-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm15-02-502-durbal>

### PM15-02-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/AH1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	weight	Y	Yc	nmax [min-1]	C	C0
PM 15 -02	-502	15	M 20 x 1.5	18.5	42	26	20	14		0.273	2.07	2.17	975	5485	3270

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507644
Inside diameter	15 mm
Outside diameter	42 mm
Thickness	20 mm
Type	SA
Weight	273 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE