


SA Rod end PM15-02-501-DURBAL - PM15-02-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm15-02-501-durbal>


PM15-02-501



male thread:
long-term lubrication, low maintenance, shields



DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]						
type	type	type	type	type	type	type	type	type	type	type				
PM 15 -02 -501	15	M 20 x 1.5	18.5	42	26	20	14							
measurements [mm]		weight	calculation-factors	rotational speed limit	basic load rating	dyn. stat.								
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	Y	Y ₀	n _{max} [min ⁻¹]	C [N]	C ₀ [N]	C ₀ [lbf]
PM 15	36	30	73.5	3.0	2.5	6.5	0.273	2.07	2.17		975	5485	3270	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507651
Inside diameter	15 mm
Outside diameter	42 mm
Thickness	20 mm
Type	SA
Weight	273 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE