

SA Rod end PM17-00-502-DURBAL - PM17-00-502-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm17-00-502-durbal>

PM17-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight		rotational speed limit		basic load rating		
type	sp. hand thread	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C [N]	C0 [N]	dyn.	stat.	
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16										
measurements [mm]		weight		rotational speed limit		basic load rating												
type	l1	l2	l3	h1	h2	u	z	α [°]	weight [kg]	Y	Yc	nmax [min-1]	C [N]	C0 [N]	dyn.	stat.		
PM 17	62,5	36	105	3,5	2,5	7,0	0,401		2,35	2,46		875	5575	2680				

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507675
Inside diameter	17 mm
Inside diameter	0.669" inch
Outside diameter	48 mm
Outside diameter	1.89" inch
Thickness	22 mm
Thickness	0.866" inch
Type	SA
Weight	401 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE